

**OUR LIFT SYSTEMS** 

## **WORLDWIDE ESTABLISHED**



High-quality lifting solutions for more than 30 years

#### **DEAR CUSTOMERS!**

Lehner Lifttechnik - Welcome to a world of barrier-free mobility. All our daily efforts are aimed at enabling the users of our products to live a barrier-free life.

Since my father founded the company over 30 years ago, our team has been working to make everyday life easier for people with mobility impairments with our reliable lifts.

We stand for affordable and at the same time high-quality lift systems. We always aim to offer our customers outstanding products at attractive prices. As a full-range supplier, our portfolio offers 13 lift solutions for a wide variety of situations. In addition to chair stairlifts and platform stairlifts, this also includes vertical platformlifts.

Thanks to the use of high-quality components and robust constructions, our products convince with durability and smooth operation. Manufacturing according to the highest European standards as well as well thought-out safety features ensure reliable use for years.

We are proud to be able to give people back a bit of independence with our lifting solutions.



Christian Lehner Managing Director



80 COUNTRIES SERVED



>45,000

**LIFTS** 



95 EXPORT IN PERCENT



32
YEARS OF
EXPERIENCE




353
SALES
PARTNERS

## **PRODUCT PORTFOLIO**



Discover our wide range of lift systems






#### **PLATFORM STAIRLIFTS**

10 Delta

11 | Stratos

12 Omega











ESSENTIAL











Chair stairlifts | 6/7










Loading capacity	130 (optional 145) kg		
Drive system	Rack and pinion		
Motor	24 V DC, battery driven		
Gradient	0 - 52°		
Speed	0.06-0.12 m/s		
Max. rail length	35 m		
Noise level	Under 50 dB		
Temperature	+45 to -15 °C		
Power supply	1 × 230 V / 50-60 Hz		
Certificate	TÜV certified to EN 81-40:2020		






## **ESSENTIAL**












#### **ALL-ROUNDER**

The advantage of chair stairlifts is their space-saving design compared to other lifts. They can be installed in almost all staircases and do not require any structural changes on site.

Loading capacity	140 kg		
Gradient	30 - 55°		
Speed	0.08 m/s		
Motor	24 V DC, battery driven		
Drive system	Rack and pinion		
Fold-up width	273 mm		
Fold-out width	546 mm		
Power supply	1 × 230 V / 50-60 Hz		












## **DELTA**



Design lift with rack and pinion drive for straight stairs



## **STRATOS**



Platform lift with rack and pinion drive for curved stairs

Platform stairlifts | 10/11



## **OMEGA**



Specialist for the narrowest staircases



## **POSSIBILITIES**

Delta, Stratos, Omega

Elevators & Escalators

Platform stairlifts | 12/13






#### **TÜV CERTIFIED**

Our platform stairlifts are TÜV certified according to the current EU standard **EN 81-40:2020**.







#### **CONTROL**

- \_\_\_\_ Landing control
  - As handheld control or fixed to the wall
- 2 Handset on spiral cable
  For comfortable operation while driving
- Joystick Integrated on the platform



## **SPECIFICATIONS**



Platform stairlifts

	DELTA	STRATOS	OMEGA	
Loading capacity	225 (optional 300) kg	225 (optional 300) kg	225 (optional 300) kg	
Platform sizes (standard)	700 x 750, 750 x 850, 800 x 900, 800 x 1000 mm	700 x 750, 750 x 850, 800 x 900, 800 x 1000 mm	700 x 750, 750 x 850, 800 x 900, 800 x 1000 mm	
Platform sizes (special)	Max. 900 x 1300 mm	Max. 900 x 1300 mm	Max. 900 x 1300 mm	
Gradient	0 - 52°	0 - 47°	0 - 67°	
Speed	0.06 - 0-12 m/s	0.06 - 0.1 m/s	0.06 - 0.15 m/s	
Noise level	Under 60 dB	Under 60 dB	Under 60 dB	
Temperature	+45 to -15 °C	+45 to -15 °C	+45 to -25 °C	
Folded width	300 mm	360 mm	275 mm	
Power supply	1 × 230 V / 50-60 Hz	1 × 230 V / 50-60 Hz	1 × 230 V / 50-60 Hz	
Standard colour	RAL 9007 RAL 7035	RAL 9007 RAL 7035	RAL 9007 RAL 7035	
Rack and pinion drive with 24 V motor on platform	✓	✓		
Cable pull system with 3 x 400 V motor at rail end			✓	
Drive engine	0.5 kW	0.5 kW	1.1 - 2.2 kW	
Max. rail length	30 m	35 m	85 m	
Certificates	TÜV certified according to EN 81-40	TÜV certified according to EN 81-40	TÜV certified according to EN 81-40	
Dimensions (min)	870 870 700 880	750	955 955	













## LIFTBOY 1-3



For height differences up to 970 mm













## LIFTBOY 4



Mobile lift for height differences up to 1400 mm

Vertical platformlifts | 16/17





#### **FUNCTIONALITY**

- Safety is top priority: This is guaranteed by the integrated emergency lowering
- Optimally adaptable to varying demands thanks to the width adjustable ramp (upper stop)
- Intuitive control on the outside of the lift including stop button



## LIFTBOY 5



For height differences up to 1300 mm



#### EFFICIENT ALTERNATIVE

The need for a lift system often arises unexpectedly and must be met quickly. Vertical platform lifts are then an optimal choice for low lifting heights.

In contrast to escalators, they convince with short delivery times and lower costs.





## **Control**Either on platform incl. display with status indication or with radio remote controls



## **SPECIFICATIONS**



Liftboy 1-5

Vertical platformlifts | 18/19

	TYPE 1	TYPE 2	TYPE 3	TYPE 4 S	TYPE 4 L	TYPE 5
Max. lifting height (mm)	595	830	970	1000	1400	1300
Min. platform height (mm)	100	120	135	182	250	125
Platform width inside (mm)	713	800	800	845	862	900/1100
Platform width outside (mm)	810	924	924	1233	1188	1150/1350
Platform length inside (mm)	1170	1495	1495	1500	1410	1400
Platform length outside (mm)	1180	1505	1505	1628	1571	1572
Loading capacity (kg)	180	300	240	300		315
Speed (mm/s)	10		17		25	
Standard colour RAL 7035	✓		✓		✓	
Standard colour RAL 9007	✓				✓	
1 x 230 V / 50-60 Hz power supply	✓				✓	
24 V actuator, scissor mechanism	✓		✓			
24 V actuator, double scissor mechanism				<b>√</b>	✓	
2 x 12 V / 9 Ah battery			✓		/	✓
Safety curtain		✓		✓		✓




#### **USER VIDEO**

In the Liftboy 1-3 user video, we show the compact lift in use. Convince yourself of the diverse possibilities of the popular lift:

# **SIGMA**For height differences up to 3000 mm





## **SIGMA**

## Flevators & Escalators


Aesthetics and safety combined in one product

Vertical platformlifts | 20/21









Loading capacity	385 kg		
Lifting height	650 - 3000 mm		
Max. number of stops	4		
Platform size	1100 x 1400 mm		
Drive system	Double chain drive		
Min. platform height	50 mm		
Standard colour	RAL 9022		
Noise level	Under 60 dB		
Temperature	+45 to -15 °C		
Drive engine	1.0 kW		
Power supply	1 x 230 V		
Emergency power supply	Integrated as standard		

## **ELEVEX**

For height differences up to 1829 mm






## **OPTIONAL AVAILABLE**



Side exit at upper landing Door at upper landing External landing control/s

Loading capacity	340 kg		
Lifting height	Type 1: 1219 mm   Type 2: 1829 mm		
Min. platform height	70 mm		
Platform size	914 x 1372 mm		
Drive system	Screw		
Speed	0.04 m/s		
Noise level	Under 60 dB		
Temperature	+45 to -30 °C		
Drive engine	0.75 kW		
Power supply	1 × 230 V / 50 Hz		
Conformity	Machinery Directive 2006/42/EC		





## **DELPHIN**



#### Poollift up to 1600 mm lifting height












#### **INSTALLATION**

No underwater installation is necessary, one attachment point at the edge of the pool is sufficient. The lift is operated with domestic water pressure.







Variant B: Screwed bracket

Loading capacity	130 kg
Lifting height standard	1220 mm
Lifting height optional	1067 to 1600 mm
Water pressure min.	4 bar
Water depth min.	1150 mm
Material	AISI 316 stainless steel

## **STAIRCLIMBERS**



Simple transport method for straight flights of stairs

Special lifts | 24/25



#### **HIGHLIGHTS**

■ Unique:


The only self-propelled stairclimber

■ Easy:

Only a small adaptation necessary

Compact:

Easy and safe to transport





#### **HIGHLIGHTS**

■ Strong:


Use with heavy electric wheelchairs

Versatile:

Ideal for use in public buildings

Durable:

High quality product for long usage





#### **HIGHLIGHTS**

Mobile:


Can be used on a wide range of stairs

Powerful:

Up to 30 floors without effort

Stable:

Robust construction for safe use



	STAIRMAX	PUBLIC	SA-3	SA-S
Loading capacity	110 kg	200 kg	160 kg	150 kg
Net weight	54 kg	115 kg	65 kg	59 kg
2 x 6 V/20 Ah battery	✓	✓	✓	✓
Max. gradient	35°	35°	35°	35°
Speed	7 m/min	8 m/min	8 m/min	8 m/min
Indoor use	✓	✓	✓	✓
Outdoor use	✓	✓	✓	✓

## **SPACE FOR NOTES**



Write down your take-aways here







Official partner of:



Loc 1: Antelias, Seaside, SSS Bldg, fifth floor beside AISHTI.

Loc 2: Bchamoun, Behind Louise Wegmann School, Andalos St. - SSS Bldg.

Tel: +961 71 260 007 Email: sales@sss-lb.com

www.sss-lb.com

Platform stairlifts

Chair stairlifts

Vertical platformlifts

Special lifts