

PRODUCT DATA SHEET

Lightning protection systems

Lightning Protection System (LPS) conductors

Code: 6400118-70

Description: Ø8mm hot dip galvanized steel solid round conductor (50m coil), code 6400118-70

Application

Hot dip galvanized steel (St/tZn) solid round conductor used as air termination conductor and down conductor.



Technical characteristics - Installation instructions

Diameter	8 mm.
Cross sectional area	50 mm ² .
Core material	Steel (St).
Coating material	Zinc (Zn).
Zinc coating weight	>350 gr/m ² .
Type of coating method	Hot dip.
Electrical resistivity	<0,25 µΩm.
Tensile strength	290 - 510 N/mm ² .
Installation	Above ground, embedded in concrete.
Can be connected above ground with	Al, Stainless Steel (SSt), St/tZn.
Can be connected in concrete with	Cu, Cu-A (copper alloy), Cu/eSn, SSt (Stainless Steel), St/eCu, St/tZn.
Straightening	For straightening can be used straightener, ELEMKO code 6900100.

Testing as per IEC EN 62561

The component has successfully passed the testing requirements of standard IEC ?? 62561-2 "Lightning protection system components (LPSC) – Part 2 : Requirements for conductors and earth electrodes".

Test report No **31317** by accredited laboratory as per ISO 17025.

ELEMKO management systems

• ISO 9001

• ISO 14001

• ISO 45001

Country of Origin

Greece

Needed accessories

Clamps (e.g. 6201810), fasteners (e.g. 6101100, 6130104) for the spacing consult fasteners' installation instructions

Unit: meter / Package: 50 m approx. / 0,395 kg/m

We reserve the right to introduce changes in the component due to technical evolution.

