



## SSG-100S



### GENERAL DESCRIPTION

Optima sliding speed gates provide aesthetic and effective control of entry or exit at kinds of toll collection systems like train/metro stations, and access control for commercial centers, stadiums, schools, government and private sector buildings etc.

### SYSTEM SPECIFICATIONS

- Main body and lateral lids are AISI 304-grade stainless steel.
- Top cover and flaps are tempered glass.
- Lateral covers are removable for easy maintenance.
- Motor start and stop control is maintained by Optima PLC controller.
- Low power consumption and silent running.
- Compatible with all access control systems.
- Turnstile is equipped with an alarm system which senses forbidden and reverse direction passing.
- Turnstiles closes flaps by itself after adjusted time if a valid card is presented but person not passed.
- All the obstacles in the passage are sensed with photoelectric sensors.
- Indoor use only.



## ENVIRONMENTAL CONDITIONS AND POWER REQUIREMENT

Between -15°C and +65°C, 95% non-condensing humidity; 220-240 VAC, mono phase, 50-60 Hz.

## OPTIONAL ACCESSORIES

- Push button box.
- Logo print on the flaps.
- Card reader system.
- Digital Counter.
- Card reader mounting plate inside or on the turnstile.
- Card reader mounting plate with pedestal.
- Stainless steel railing.
- Uninterrupted power supply (UPS)
- SCADA or any control system: It is turnstile to change and check the position of the turnstile with a touch screen control panel, mobile devices (ios-android), computer, etc.

## MAIN BODY MEASUREMENTS

